STEP ONE



Color - Red : 255 Stroke - 0.00001

Color - Grayscale Fill Fill - Any Color

Color - Blue: 255 Stroke - 0.00001

DOCUMENT SET UP

ARTBOARD SIZE

Set Artboard size to match the Laser bed

Laser 1 - 24" x 18" Laser 2 - 24" x 18" Laser 3 - 24" x 18" Laser 4 - 24" x 48" Laser 5 - 48" x 24"

COLOR DOCUMENT

Set color document mode to RGB

File Tab > Document Color Mode > RGB Color

DOCUMENT PRINTING

o print when ready. In nt dialog, click on SETUP. > Print

p your material setting, n PREFERENCES.

STEP TWO

| Print | | 🥪 Print | × | DUCU |
|--|--|--|--|---|
| | | General | | Cond to |
| Genera Marka nd Bleed Output Graphy s | Corpus, N.S.2. 100 Corpus, C | Select Printer Adobe PDF Fax ILS12.150D | ➢ Microsoft Print to PDF ➢ Microsoft XPS Document W ➢ NPI40B07F (HP LaserJet 700 | the prin File Tab |
| Color Management | Media Size: Defined by Driver | Status: Ready Location: Comment: | Print to file Preferences | To setu click or |
| Document 65 ns 11 n | Captons Protections Protections Protections Scale: V Scale: V Scale: | Page Range All Selection Pages: Current Page | Number of copies: 1 | |
| Setup | | | Print Cancel | |

STEP THREE

| | | MATERIAL SETUP | | |
|--|---|---|--|--|
| Materials Database Manual Control | | Choose your MATERIAI | | |
| Selected: Standard Material General Medium Woods 381451 Find Wood Hard Wood Hard Wood Hard Wood Hard Wood Hard Woods Hard Wood Hard Woods Hard Wood Hard Hard Wood Har | Intensity Adjustment Rester Constrained by the state of | If you cant find your material, talk to the monitor. Always run a "test" with 0% adjustment. Increase or decrease power accordingly for your material | | |
| Normal Standard | | Add in Material THICKNESS. | | |
| Material Thickness O.125 " Merge Pages | Apply Defaults : Load Save QK Cancel | 1/2" = 0.5"1/32" = 0.013"1/4" = 0.25"3/8" = 0.5"1/8" = 0.125"3/16"=0.1875"1/16" = 0.063"3/32"=0.09375' | | |